

OTHER LEAK TIPS

Take a few minutes today to save tomorrow!

- Check your toilet tank at least twice a year.
- Turn the water off. Don't let it run when you wash, brush your teeth, shave or wash your car.
- Water your lawn in early morning - one inch a week is good for your grass
- Take shorter showers or a bath

- Run full loads of dishes and clothes.
- Water plants, not the sidewalk.
- Be smart, fix leaks




FOR MORE KITS

KINGSCOTE CHEMICALS, INC. • 1-800-394-0678

HOME WATER-SAVING KIT LEAK DETECTIVE™ • DAILY •

IS YOUR WATER BILL TOO HIGH?



You may think those little leaks in your bathroom don't amount to a drop-in-the-bucket. Not so. The sneakiest drip can be found

in your bathroom toilet. Toilet tank leaks, almost undetectable to the naked eye, can add \$25.00 or more to your monthly bill.

Take 15 Minutes to Save Gallons of Water Everyday!




- Less Water Down the Drain
- Find Toilet Leaks
- Save With Each Flush

STOP THE DRAIN ON YOUR DOLLARS!

TOILET LEAK DETECTION


Leaks always get larger and cost you more the longer you wait.



LEAK TEST

- 1 Wait 5-10 minutes after the last flush cycle to perform the leak test.
- 2 Remove the cover. Gently drop one Leak Detective tablet into tank. Do not flush.
- 3 Wait 15-20 minutes.
- 4 If blue dye color appears in bowl, you have a leak. (Don't worry, it won't stain the bowl).

SOURCES OF THE LEAK MAY BE:



- 1 The flapper valve and valve seat (A) have deteriorated or corroded.
- 2 The flushing arm and lift chain (B) are not working properly.
- 3 The water level in the tank is too high and spills into the overflow tube (C).
- 4 The float rod, ballcock and/or float ball (D) are corroded.

Replacement parts are available at hardware and plumbing supply stores or consult your local plumbing professional.